



TABLE 1

| SPACER THICKNESS & LENGTH TABLE | | |
|---------------------------------|-------------------|---------------|
| PIPE DIAMETER (NOMINAL) | MINIMUM THICKNESS | SPACER LENGTH |
| 25 - 38mm | 2mm | 150mm |
| 50mm | 2mm | 300mm |
| 75 - 100mm | 2.3mm | 300mm |
| 150mm | 3mm | 300mm |
| 200mm | 3.8mm | 300mm |
| 250mm | 4.3mm | 300mm |
| 300mm | 4.8mm | 400mm |
| 350mm | 5.8mm | 400mm |
| 400mm | 6.4mm | 400mm |
| 500mm + | 8mm | 400mm |

NOTE

1. APPLICATIONAL SPACER ON METALLIC PIPE REQUIRED WHEN DIM 'A' AND/OR DIM 'B' IS LESS THAN 300mm OR AS SPECIFIED BY DESIGNER.
2. REFER TO TABLE 1 FOR RECOMENDED SPACER DIMENSIONS.
3. SPACER SHALL MEET THE REQUIREMENTS OF REGION OF PEEL WATERMAIN, STORM SEWER AND SANITARY SEWER DESIGN CRITERIA ADDENDUM, SECTION 3.6.
4. FOR BONDED FOREIGN PIPE ARRANGEMENTS, SEE DRAWING NUMBER 3-2-3 FOR TEST STATION AND CROSS BONDING DETAIL.