

19/C (VEH.)

1. R1 - (N/S/E/W) LEG RED
2. R2 - (N/S/E/W) LEG L.T. RED (PROT)
3. R3 - (N/S/E/W) LEG BIKE RED
4. R4 - (N/S/E/W) LEG DON'T WALK
5. R5 - SPARE
6. Y1 - R1 - (N/S/E/W) LEG AMBER
7. Y2 - (N/S/E/W) LEG L.T. AMBER (PROTECTED / PROTECTED PERMISSIVE)
8. Y3 - (N/S/E/W) LEG BIKE AMBER
9. Y4 - SPARE
10. Y5 - SPARE
11. BL1 - (N/S/E/W) LEG GREEN
12. BL2 - (N/S/E/W) LEG L.T. GREEN (PROTECTED / PROTECTED PERMISSIVE)
13. BL3 - (N/S/E/W) LEG BIKE GREEN
14. BL4 - (N/S/E/W) LEG WALK
15. BL5 - SPARE
16. W1 - NEUTRAL
17. W2 - SPARE
18. BLK - SPARE
19. O - SPARE

NOTE

1. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH DRAWINGS 4-3-2 AND 4-3-1-B.

ALL DIMENSIONS IN MILLIMETRES
UNLESS OTHERWISE NOTED



PUBLIC WORKS
STANDARD DRAWING

REV. DATE: DECEMBER 2018

APPROVED BY

DRAWN BY

GK

TSS SECTION

TRAFFIC SIGNAL CONDUCTOR DESIGNATION
(19/C) - 4 GROUP CONFIGURATION

STD. DWG. NUMBER

SCALE

4-3-3-B

N.T.S.